Model PQ/PQS/PGS
Intermediate Proofer

Every component assures you satisfactory function for better dough quality. Available for various type of dough, e.g. bread, bun, or roll.

Model PQ

Model PQS

OSHIKIRI

Intermediate Proofer　　Model PQ/PQS/PGS

■Model PQ sample diemnsions









■Model PQS sample dimensions

Infeed and discharge section are to be designed in accordance with Customer's requirement. Contact us for detailed infromation.

■Specifications

Model	No. of pockets	Dough weight	Type of infeed	Rotation	No. of invalid trays	Capacity(pcs/h) (15 min. proofing)	Main motor
PQ	8	30 - 250g	Single row belt conveyor	8 rotation	6	2,000 (70B)	0.4kW 4P 200V
					7	2,500 (84B)	
PQS	8	30 - 300g	Pallet	1 rotation	17	2,600 - 8,300(8P)	0.75kW 4P 200V (～185B)
	12					3,850 - 12,150(12P)	1.5kW 4P 200V (205B～)
PGS	8	30 - 400g	Pallet	1 rotation	14	2,100 - 6,600(8P)	0.75kW 4P 200V (～180B)
	12					3,050 - 9,700(12P)	1.5kW 4P 200V (188B～)

Note) Specifications and dimensions are subject to change without prior notice.
Note) Transformer might be needed depending upon the specifications.

OSHIKIRI MACHINERY LTD. https://www.oshikiri.com/

4, Kirihara-cho, Fujisawa-shi, Kanagawa, 252-0811 Japan
Phone: 0466-44-6184 Fax: 0466-44-6187 E-mail: intl@oshikiri.com

Oshikiri Corporation of America
10425 Drummond Road, Philadelphia, Pennsylvania 19154-3898
Phone: 215-637-6005 Fax: 215-637-6041 E-mail: sales_oca@oshikiri.com

OSHIKIRI Website

25.03.19 OSHIKIRI P-081-6